

YOUR CHEMICAL  
SOLUTION  
PROVIDER



StarMarine

C H E M I C A L S

# ELECTRIC SLOW

**Odorless, non-emulsifying degreasing agent and non-conductive electro cleaner**

- \* Special degreasing agent for the removal of oil and grease from machines and motor parts, transmissions, ball bearings, gear wheels, metal parts, electrical components, etc.
- \* Odorless.
- \* Contains no chlorinated hydrocarbons or other harmful chemicals.
- \* Does not emulsify in water - the polluted oil can be separated by means of an oil/water separator.
- \* High flash point.

## Application

Electric Slow can be applied with a brush or by spraying the parts to be cleaned. This product can also be used by filling an immersion bath to clean extremely dirty parts. The high flash point and the fact that it is practically odorless makes Electric Slow a pleasant and problem free product.

## Directions for use

### **Immersion Baths**

Electric Slow is used undiluted and unheated in immersion baths. Put the parts to be cleaned in the bath and soak for several hours. Thereafter, take the parts out of the bath and spray off with a forceful waterjet.

Attention: parts that need to be rust free and dry (such as electrical components) should not be sprayed clean with water but with clean Electric Slow and afterwards should be blow-dried completely because of fire risk if residues are left behind.



StarMarine

C H E M I C A L S

Bunschotenweg 134 - 3089KC Rotterdam - Harbournumber 2696 - The Netherlands  
Tel: +31(0)105925831 Mob: +31(0)643065133 e-mail: [info@starmarine.nl](mailto:info@starmarine.nl)  
VATnr. NL859322968B01 Chamber of Commerce: 73019704

## **General Cleaning**

For the cleaning of dirty parts and surfaces use Electric Slow undiluted. Moisten the parts to be cleaned thoroughly with the product. Depending on the measure of dirt, soak the product for 5 to 60 minutes, brush in between. After this, rinse thoroughly with water.

Attention: parts that need to be rust free and dry (such as electrical components) should not be sprayed clean with water, but with Electric Slow and afterwards should be blow dried completely to avoid fire risk.

## **Attention**

Cold cleaners should only be used in combination with oil/water separators.

To guarantee an optimal oil/water separation, cold cleaners should never be used with greater amounts of emulsifying cleaners (e.g. of HP Cleaner) if the waste is passing oil/water separators.

## **Properties**

Clear, odourless, fluid neutral degreasing agent based on among other things, high boiling aliphatic hydrocarbon. Electric Slow evaporates without residue. Electric Slow can be used on most metals, synthetic material, rubber and hardened metals, electrical components.

Specific gravity (20° C) : 0.79  
Flashpoint : >62° C  
pH : 7

*For detailed information on safety and health, please refer to Material Safety Data Sheet and / or Product label.*

Star Marine is a specialist chemical manufacturer and any directions for the use and application of its chemicals are provided in good faith. This information is based on experience and research but is not intended to be a definitive statement for the use of the chemical or to be taken as complete process advice. While the company, its management and employees will share what knowledge they have and make recommendations, this information can never give rise to liability or consequential damage from third parties. Any information provided regarding the chemical does not exempt the customer from examining the product and its directions for use to determine the suitability themselves for its intended purpose.

